



# DISTRIBUTION BOARDS

## THERMOPLASTIC - ABS



### Technical Features

- Degree of protection: IP54 - P65\*.
  - Resistance to impact: IK08.
  - Glow wire resistance: 650 °C.
  - Dimensional stability: -35 °C / +65 °C.
  - Materials:
    - Boards: HB ABS. RAL7035.
    - Mounting Plate: Galvanised steel 1 mm.
  - Resistance: Chemical agents, alkali, oils, etc. Recommended for indoor installations.
- \* IP65 for ABS302013 and ABS322515 references.



### Thermoplastic distribution boards (ABS) Opaque door - With mounting plate

| Reference | Dimensions<br>Hight x Width x Deep | Units | Weight<br>(Kg) |
|-----------|------------------------------------|-------|----------------|
| ABS302013 | 300x200x130                        | 1     | 1,70           |
| ABS352515 | 350x250x150                        | 1     | 2,20           |
| ABS403017 | 400x300x170                        | 1     | 3,00           |
| ABS403022 | 400x300x220                        | 1     | 3,40           |
| ABS503519 | 500x350x190                        | 1     | 4,30           |
| ABS504017 | 500x400x170                        | 1     | 4,30           |
| ABS504024 | 500x400x240                        | 1     | 5,60           |
| ABS604020 | 600x400x200                        | 1     | 6,00           |
| ABS705025 | 700x500x250                        | 1     | 10,10          |
| ABS806026 | 800x600x260                        | 1     | 13,50          |

### Included accessories

- Metal mounting plate.
- Wall-mounting support.
- Polyamide key in triangle.



### Accessories

| Reference | Description          | Units |
|-----------|----------------------|-------|
| 29580     | Manual lock with key | 1     |

