

ARGENTA PLUS SERIES

IP55 STEEL FLOOR-STANDING COMBINABLE CABINETS (ENL)

Description: IP55 COMBINABLE FLOOR-STANDING CABINET (ENL) 1800x1600x500
DOUBLE OPAQUE DOOR WITHOUT PLATE

Reference:
ENL18016050PO/DC

Characteristics:

Product type:	Steel floor-standing combinable cabinets (ENL)
Dimensions cabinet:	(AxBxC) 1800x1600x500 mm
Installation:	Surface
Type of door:	Symmetrical opaque double door
Locking:	Double lock. 2-point 1/4 turn interior double lock and double-bit exterior insert with handle in RAL 7016 grey
Finish:	Coated with primer, and hardened polyester paint, textured, with UV protection
Colour:	RAL 7035
Mounting plate:	Without mounting plate
Weight (kg):	174,2
Materials:	Cold-rolled steel EN 10130+A1
Thickness:	Enclosure: 1,5 mm. Door: 2 mm. Cable entry lid: 1,2 mm.
Sealing gasket:	Injected polyurethane sealing gasket
Door material:	
Capacity:	
Max. cabinet load:	
Max. mounting plate load:	
Max. door load:	

Technical data:

Degree of protection:	IP55
NEMA degree of protection:	NEMA 1, 12
Resistance to impact:	IK10
Ambient temperature range:	-25 °C / +60 °C
Maximum operating voltage:	1000 V AC / 1500 V DC

Certificates and standards:

Directive:	2014/35/EU
Standards:	IEC 62208, IEC 61439-1
Certificates:	UL508A



Codes:


EAN:	8431044051598
Customs tariff number:	85.38.10.00
ETIM 8.0:	EC000261

ARGENTA PLUS SERIES

IP55 STEEL FLOOR-STANDING COMBINABLE CABINETS (ENL)

Description: IP55 COMBINABLE FLOOR-STANDING CABINET (ENL) 1800x1600x500 DOUBLE OPAQUE DOOR WITHOUT PLATE

Reference: ENL18016050PO/DC



Standard drawing

Detailed drawing: <https://www.ide.es/downloads/planos/pdf/ENL18016050PODC.pdf>
<https://www.ide.es/downloads/planos/dxf/ENL18016050PODC.dxf>
<https://www.ide.es/downloads/planos/stp/ENL18016050PODC.stp>

Cable entry: (Width x Depth) 1370x410 mm
Wall fixing: -
Inside usable space: (HeightxWidthxDepth) 1710x1510x410 mm
No. Hinges:

Body to be flush-fitted: -
Wall fixing material:
Glass door with transparent panel: -
Door profiles:

Sustainability:

RoHS - REACH

Supply:

Supplied on pallets, protected with honeycomb cardboard corner pieces and shrink-wrap film. It includes 2 lifting eyebolts fitted and cable entry lids. Supplied without mounting plate or side panels.

Product end of life:

It does not require specific recycling operations.

Recommended applications:

Industrial environments, manufacturing companies requiring a high degree of protection against dust, splashes and impacts.