

ARGENTA PLUS SERIES

IP55 STEEL FLOOR-STANDING COMBINABLE CABINETS (ENL)

Description: IP55 COMBINABLE FLOOR-STANDING CABINET (ENL) 2200x800x800
OPAQUE DOOR WITHOUT PLATE

Reference:
ENL2208080PO/SP

Characteristics:

Product type:	Steel floor-standing combinable cabinets (ENL)
Dimensions cabinet:	(AxBxC) 2200x800x800 mm
Installation:	Surface
Type of door:	Single opaque door
Locking:	4-Point double-bit insert with retractable handle in RAL 7016 grey
Finish:	Coated with primer, and hardened polyester paint, textured, with UV protection
Colour:	RAL 7035
Mounting plate:	Without mounting plate
Weight (kg):	115,1
Materials:	Cold-rolled steel EN 10130+A1
Thickness:	Enclosure: 1,5 mm. Door: 2 mm. Cable entry lid: 1,2 mm.
Sealing gasket:	Injected polyurethane sealing gasket
Door material:	
Capacity:	
Max. cabinet load:	
Max. mounting plate load:	
Max. door load:	

Technical data:

Degree of protection:	IP55
NEMA degree of protection:	NEMA 1, 12
Resistance to impact:	IK10
Ambient temperature range:	-25 °C / +60 °C
Maximum operating voltage:	1000 V AC / 1500 V DC

Certificates and standards:

Directive:	2014/35/EU
Standards:	IEC 62208, IEC 61439-1
Certificates:	UL508A



Codes:


EAN:	8431044044545
Customs tariff number:	85.38.10.00
ETIM 8.0:	EC000261

ARGENTA PLUS SERIES

IP55 STEEL FLOOR-STANDING COMBINABLE CABINETS (ENL)

Description: IP55 COMBINABLE FLOOR-STANDING CABINET (ENL) 2200x800x800 OPAQUE DOOR WITHOUT PLATE

Reference: ENL2208080PO/SP



Standard drawing

- Detailed drawing:**
- <https://www.ide.es/downloads/planos/pdf/ENL2208080POSP.pdf>
 - <https://www.ide.es/downloads/planos/dxf/ENL2208080POSP.dxf>
 - <https://www.ide.es/downloads/planos/stp/ENL2208080POSP.stp>

Cable entry:	(Width x Depth) 570x710 mm	Body to be flush-fitted:	-
Wall fixing:	-	Wall fixing material:	-
Inside usable space:	(HeightxWidthxDepth) 2110x710x710 mm	Glass door with transparent panel:	-
No. Hinges:		Door profiles:	

Sustainability:

RoHS - REACH

Supply:

Supplied on pallets, protected with honeycomb cardboard corner pieces and shrink-wrap film. It includes 2 lifting eyebolts fitted and cable entry lids. Supplied without mounting plate or side panels.

Product end of life:

It does not require specific recycling operations.

Recommended applications:

Industrial environments, manufacturing companies requiring a high degree of protection against dust, splashes and impacts.